

Automatic pneumatic underpinner with sliding nailing head

JUMBO JOINT AUTOMATICA 3 POSITIONS

Pneumatic electric underpinner for joining small, medium and big frames with a minimum section of 8x5 and a maximum section of 110x100. The JUMBO JOINT AUTOMATICA is highly flexible and suitable for any type of moulding as it blocks the angle to join and through the staple insertion unit mounted on a sliding nailing head, it inserts the staples up to 3 standard positions. It can work in both manual and automatic mode and it's equipped with all the following independent adjustments: pushing strength of the frontal presser; clamping strength and descent speed of the upper presser; tilting/opening angle adjustment of the fences; manual or automatic mode; insertion into 3 different positions of parallel and superimposed

staples without unclamping the frame; self-levelling pressers especially suitable for clamping wide (more than 40 mm) and shaped frames; device for the exclusion of one of the pressers to work mouldings less than 40 mm wide. It's standardly equipped with a pneumatic staple-pusher that stops the machine when the staples are over indicating the empty loader. To operate easily, all controls and adjustments are in a frontal control

panel including the display programmer.

JUMBO JOINT AUTOMATICA EC 2 POSITIONS

This is a simplified version of the model above, that works in automatic with 2 positions for inserting staples in mediumsmall mouldings, from 8x5 mm to 50x80 mm., and up to 110x100 mm in manual mode.

The JUMBO AUTOMATICA EC 2 POSITION is standardly supplied with upper single presser, fixed fence and spring staple-pusher.

The performances of the underpinner increase notably if it is provided with self-levelling pressers and adjustable fence, that for this model are optional.

ILLUSTRATED MODEL CORRESPONDS TO THE

JUMBO JOINT AUTOMATICA EC 2 POS.

IT IS EQUIPPED WITH OPTIONAL SELF-LEVELLING

PRESSERS DEVICE

JUMBO JOINT MANUALE EC



Pneumatic version of the previous model, it is the basic machine for framers and carpenters that works a wide range of profiles both for dimensions and sizes.

Easy to use, it's standard equipped with single presser, fixed fence and mechanical staple pusher.

The performances of the underpinner increase notably if it is provided with self-levelling pressers and adjustable fence, that for this model are optional.

Available with 120 or 150 mm staples insertion's stroke.

A-Plus Automation s.r.l. Via Selva, 23/25 47122 - Forlì (FC) Italy Phone +39 0543 481142 Fax +39 0543 480770

Email info@a-plusautomation.com
Web www.a-plusautomation.com





Automatic pneumatic underpinner with sliding nailing head

JUMBO JOINT AUTOMATICA 3 POSITIONS

Data Sheet



















min. 8x5mm max. 110x100mm

7-10-12-15 mm

250 mm

8 bar

220V 50Hz 110V 60Hz 300W

3,30 NI at 7 bar

30/minute 35 x 70 x 40 cm

41 Kg

JUMBO JOINT AUTOMATICA EC 2 POSITIONS

Data Sheet



















min. 8x5mm max. 50x80mm

7-10-12-15 mm

250 mm

8 bar

220V 50Hz 110V 60Hz 300W

3,25 NI at 7 bar

30/minute

35 x 55 x 40 cm

37 Kg

JUMBO JOINT MANUALE EC

Data Sheet



min. 8x5mm max. 110x100mm









8 bar











130x100mm

7-10-12-15 mm

250 mm

bar

3,00 NI at 7

35/minute

35 x 55 x 40 cm

33 Kg

Standard Accessories

FILTER LUBRICATOR



FENCES 120°- 135°



FENCE RISERS



CLOSET BENCH



TILTING FLOOR STAND



BALANCER



TABLE



WINGS



FIXED STAND



SELF-LEVEL PRESSERS



ADJUSTABLE FENCE



A-Plus Automation s.r.l. Via Selva, 23/25 47122 - Forli (FC) Italy

Phone Fax Email Web

+39 0543 481142 +39 0543 480770 info@a-plusautomation.com www.a-plusautomation.com

